

IRONHEART

- F O U N D R Y -



LEADTOP & DUALTOP



The IRONHEART DUALTOP & LEADTOP are the latest addition to our FOUNDRY range. Joining the already hugely successful LOUDPEDAL. These 60-Watt amplifiers serve up the power, dynamism and versatility of our critically-acclaimed IRONHEART tube range in compact, portable solutions that are practical and a lot of fun to use!

In a market currently served by generic budget amps, we have delivered a UK designed, powerful and great sounding pair of guitar amplifiers that are sure to turn heads.

James Laney - CEO

The IRONHEART FOUNDRY series has taken the sheer power and dynamism of our IRONHEART tube amps and smelted and forged their characteristics to deliver monstrous power and incredible versatility in an ultra-compact form.

Beginning with the LOUDPEDAL we now present to you the LEADTOP and DUALTOP.

DUALTOP LEADTOP



LEADTOP



DUALTOP



IRT60H



IRONHEART

- F O U N D R Y -



LEADTOP

PERFORM

A black Laney guitar amplifier is shown from a rear-three-quarter perspective. The back panel features a red LED light bar with a grid pattern, the 'Laney' logo in a white box, and various control knobs and switches. The scene is dimly lit with green and red ambient lighting.

60 WATTS

Single channel amp with clean and lead mode + BOOST

PRACTICE



Switchable Pre-Boost, with Level

Selectable Bright, Natural and Dark voicing



3 Band Passive EQ Tone Stack

VERSATILE

Effects Loop (Transformer Isolated)

100-240V Universal
Voltage power supply
included (24V/2.5A)



Loudspeaker out

Line Out

High and Low power modes (Low Power <1W)

Cabinet emulated Headphone Output

PORTABLE



Real IRONHEART tone
3.67Kg, (8.1 lbs)

Model	IRF-LEADTOP
Type	Guitar Amplifier Head
Input Impedance	1MΩ
Line Output Impedance	100Ω
Minimum Speaker Impedance	8Ω
Amplifier Power	60W RMS
Controls	Gain, Volume with Clean, Rhythm, Lead switch and Natural, Bright, dark switch. Input pre- boost level and footswitch with LED indicator. Bass, Middle, treble controls. On/Off soft start power switch, DI out emulation on/off and ground link switches
Inputs	6.3mm (1/4") Mono Instrument Input Jack, 3.5mm stereo aux in jack
Outputs	6.3mm (1/4") Mono Speaker Output Jack, 6.3mm FX Send (Transformer Isolated), 6,3mm FX Return jack, Balanced Male XLR DI out, 3.5mm stereo headphone jack
Power Supply	Regulated 24V 2.5A 60W DC PSU Included: centre Positive, 2.1 x 5.5 x 12mm connector type
Typical Power Consumption	60W
Unit dimensions (HWD)	163 x 292 x 184mm, (6.4" x 11.5" x 7.2")
Unit weight	3.67Kg, (8.1 lbs)
Carton dimensions (HWD)	255 x 450 x 265mm, (10" x 17.7" x 10.4") , 0.03 M3
Packed Weight	4.7Kg, (10.4 lbs)
EAN Code (Single)	5060109458541
Master Carton Dimensions (HWD)	270 x 480 x 540mm, (10.6" x 18.9" x 21.3") , 0.07 M3
Master Shipping Carton Weight	10.4Kg, (22.9 lbs)
EAN Code (Shipping)	5060109458558 (2 pcs)

IRONHEART

- F O U N D R Y -



DUALTOP

60
WATTS



TWIN channel amp with high quality Laney IRs



2 Independent Channels

FEATURE-PACKED

Switchable Pre-Boost, with Level

CH2 Bright/Normal/Dark Voicing

BCC-SECRET PATH
Reverb



CH1 with selectable ASYM/CLEAN/SYM modes

3 Band Passive EQ Tone Stack



XLR DI OUT Loaded with two, switchable high-quality Laney customs IRs 1x12" & 4x12" cabs.

Cabinet Emulated Headphone Output

Effects Loop (Transformer Isolated)

Loudspeaker out

High and Low power modes (Low Power <1W)

Footswitch input

100-240V Universal Voltage power supply included (24V/2.5A)

LOUDSPEAKER (CLASS II WIRING)

WATTS

MAX

<1W

IMPEDANCE 8-16 OHMS

24V DC 2.5A
5.5x2.1x10mm

POWER CONSUMPTION 60W

Model	IRF-DUALTOP
Type	Guitar Amplifier Head
Input Impedance	1M Ω
Line Output Impedance	100 Ω
Minimum Speaker Impedance	8 Ω
Amplifier Power	60W RMS
Controls	Two Channels both with Gain and Volume. CH1 Clean, Rhythm, Lead switch. CH2 Natural, Bright, dark switch. Input pre-boost level and footswitch with LED indicator. Bass, Middle, Treble controls. Channel select footswitch with LED indication. On/Off soft start power switch, IR Based DI out emulation on/off and ground link switches
Inputs	6.3mm (1/4") Mono Instrument Input Jack, 3.5mm stereo aux in jack
Outputs	6.3mm (1/4") Mono Speaker Output Jack, 6.3mm FX Send (Transformer Isolated), 6,3mm FX Return jack, Balanced Male XLR DI out, 3.5mm stereo headphone jack
Power Supply	Regulated 24V 2.5A 60W DC PSU Included: centre Positive, 2.1 x 5.5 x 12mm connector type
Typical Power Consumption	60W
Unit dimensions (HWD)	178 x 377 x 184mm, (7" x 14.8" x 7.2")
Unit weight	4.66Kg, (10.3 lbs)
Carton dimensions (HWD)	265 x 535 x 265mm, (10.4" x 21.1" x 10.4") , 0.038 M3
Packed Weight	5.6Kg, (12.3 lbs)
EAN Code (Single)	5060109458527
Master Carton Dimensions (HWD)	280 x 550 x 550mm, (11" x 21.7" x 21.7") , 0.085 M3
Master Shipping Carton Weight	12.2Kg, (26.9 lbs)
EAN Code (Shipping)	5060109458534 (2 pcs)